


轮胎周长参照表

轮胎圆周数据的得出方式通常有以下两种：

- 测量轮胎圆周 (L)
调整胎压到适当值，在加上体重的状态下，转动轮胎一周，然后测量其距离。



- 请参阅轮胎圆周参考表
一般而言，轮胎尺寸或ETRTO通常标示于轮胎侧面。

ETRTO	轮胎尺寸	L (mm)	L (cm)	英寸
47-203	12x1.75	935	94	
54-203	12x1.95	940	94	12
40-254	14x1.50	1020	102	14
47-254	14x1.75	1055	106	
40-305	16x1.50	1185	119	
47-305	16x1.75	1195	120	16
54-305	16x2.00	1245	125	
28-349	16x1-1/8	1290	129	
37-349	16x1-3/8	1300	130	
32-369	17x1-1/4 (369)	1340	134	
40-355	18x1.50	1340	134	
47-355	18x1.75	1350	135	18
32-406	20x1.25	1450	145	
35-406	20x1.35	1460	146	
40-406	20x1.50	1490	149	
47-406	20x1.75	1515	152	
50-406	20x1.95	1565	157	
28-451	20x1-1/8	1545	155	
37-451	20x1-3/8	1615	162	20
37-501	22x1-3/8	1770	177	22
40-501	22x1-1/2	1785	179	
47-507	24x1.75	1890	189	24
50-507	24x2.00	1925	193	
54-507	24x2.125	1965	197	
25-520	24x1(520)	1753	175	
	24x3/4 Tubular	1785	179	
28-540	24x1-1/8	1795	180	
32-540	24x1-1/4	1905	191	
25-559	26x1(559)	1913	191	
32-559	26x1.25	1950	195	
37-559	26x1.40	2005	201	
40-559	26x1.50	2010	201	
47-559	26x1.75	2023	202	
50-559	26x1.95	2050	205	
54-559	26x2.10	2068	207	
57-559	26x2.125	2070	207	
58-559	26x2.35	2083	208	

ETRTO	轮胎尺寸	L (mm)	L (cm)	英寸
75-559	26x3.00	2170	217	
28-590	26x1-1/8	1970	197	
37-590	26x1-3/8	2068	207	
37-584	26x1-1/2	2100	210	26
	650C Tubular 26x7/8	1920	192	
20-571	650x20C	1938	194	
23-571	650x23C	1944	194	
25-571	650x25C 26x1(571)	1952	195	
40-590	650x38A	2125	213	
40-584	650x38B	2105	211	
25-630	27x1(630)	2145	215	
28-630	27x1-1/8	2155	216	27
32-630	27x1-1/4	2161	216	
37-630	27x1-3/8	2169	217	
40-584	27.5x1.50	2079	208	
50-584	27.5x1.95	2090	209	
54-584	27.5x2.1	2148	215	27.5
57-584	27.5x2.25	2182	218	
18-622	700x18C	2070	207	
19-622	700x19C	2080	208	
20-622	700x20C	2086	209	
23-622	700x23C	2096	210	
25-622	700x25C	2105	211	
28-622	700x28C	2136	214	
30-622	700x30C	2146	215	
32-622	700x32C	2155	216	
	700C Tubular	2130	213	700c
35-622	700x35C	2168	217	
38-622	700x38C	2180	218	
40-622	700x40C	2200	220	
42-622	700x42C	2224	222	
44-622	700x44C	2235	224	
45-622	700x45C	2242	224	
47-622	700x47C	2268	227	
54-622	29x2.1	2288	229	29
56-622	29x2.2	2298	230	
60-622	29x2.3	2326	233	